

FCR 3

Designed to move you, the FCR line is the ultimate training tool for the athlete looking to break free of the gym.



SPECIFICATIONS

Specifications and availability subject to change without notice.

FRAME	MODEL	FCR 3
	SIZES	XS, S, M, L, XL
	COLORS	Silver/Black
	FRAME	ALUXX Butted Aluminum, Compact Road Design, Integrated Forged Headtube
	FORK	Chromoly Steel
	SHOCK	N/A
	HANDLEBAR	Butted Alloy, 25mm Rise
COMPONENTS		
	STEM	Alloy, 17 Degree Rise
	SEATPOST	Aluminum 27.2x300mm
	SADDLE	WTB Laser V Comp
	PEDALS	Resin
	SHIFTERS	Shimano ST-R225
	FRONT DERAILLEUR	Shimano FD-R443
DRIVETRAIN		
	REAR DERAILLEUR	Shimano Sora
	BRAKES	Alloy Direct-Pull
	BRAKE LEVER	Alloy Direct-Pull
	CASSETTE	SRAM PG830, 11/28T, 8-speed
	CHAIN	KMC Z72
	CRANKS	TruVativ Touro, 30/42/52T
	BBCartridge	
WHEELS		
	RIMS	Alex CR06 Double Wall
	HUBS	Formula Sealed Bearing
	SPOKES	Stainless Steel
	TIRES	Kenda Kwest, 700x32c
	EXTRAS	

FRAME TECHNOLOGY

Featuring a butted ALUXX aluminum frame and Chromoly steel fork, FCR geometry delivers equal parts performance and sure-footed positioning for spirited workout rides or confident commuting.



FEATURES

- Wide-range 24-speed Shimano Sora shifting with triple TruVativ Touro crankset
- Comfortable WTB Laser V Comp saddle
- Confident-handling Kenda Kwest 700x32c tires

MSRP **\$480.00**

FRAME GEOMETRY

ACTUAL FRAME SIZE	HEAD ANGLE	SEAT ANGLE*	TOPTUBE**	HEADTUBE	CHAINSTAY	WHEELBASE	STAND-OVER HEIGHT***
centimeters	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/42.0 cm	71.0	75.0	51.1	11.8	41.8	97.8	28.7
S/46.5 cm	72.0	74.0	53.1	14.0	41.8	98.5	29.6
M/50.0 cm	72.5	73.0	54.9	16.5	41.8	99.1	30.6
L/55.5 cm	72.5	73.0	57.5	19.0	41.8	101.7	31.8
XL/58.5 cm	72.5	72.5	60.0	21.5	41.8	103.7	32.6

*Seat angle is actual

**Tuptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire