

# FCR 1

## ROAD FITNESS

For the athlete who realizes there's more to fitness than a rack of barbells, a treadmill and a TV. An ALUXX aluminum-framed FCR gets you out of the gym and onto the open road.



### SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Blue/Brushed
	FRAME	ALUXX Aluminum, Compact Road Design
	FORK	formulaOne Composite w / alloy steerer tube
	SHOCK	N / A
COMPONENTS		
	HANDLEBAR	6061AL lowrise w/bar ends
	STEM	3D forged
	SEATPOST	formulaOne Composite
	SADDLE	WTB Laser V Race
	PEDALS	Shimano PD-M505
DRIVETRAIN		
	SHIFTERS	Shimano SL-R440
	FRONT DERAILLEUR	Shimano R440
	REAR DERAILLEUR	Shimano 105
WHEELS		
	BRAKES	TK 829A
	BRAKE LEVERS	TK RS388AV
	CASSETTE	SRAM PG 950 11/28, 9- speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano FC-4550-S, 34/50
	BOTTOM BRACKET	Shimano, external
	RIMS	Xero XSR-3
	HUBS	Xero XSR-3
	SPOKES	Xero XSR-3
	TIRES	Kenda Kontender, 700x26
	EXTRAS	

Specifications and availability subject to change without notice.

### FRAME TECHNOLOGY

Featuring a butted ALUXX aluminum frame and formulaOne Composite fork, FCR geometry delivers equal parts performance and sure-footed positioning for spirited workout rides or confident commuting.



### KEY UPGRADES (OVER FCR 2)

- Smooth-shifting Shimano 9-speed drivetrain
- Shimano M505 clipless pedals
- Lightest Xero XSR-3 wheelsset

### FRAME GEOMETRY

Actual Frame Size	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters	degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0	71.0	75.0	52.5	12.5	42.5	100.9	29.5
S/46.5	72.0	74.0	54.5	14.5	42.5	101.0	30.3
M/50.0	72.5	73.0	56.5	17.0	42.5	102.5	31.3
L/55.5	72.5	73.0	58.5	20.0	42.5	103.5	32.8
XL/58.5	72.5	72.5	60.5	22.5	42.5	104.9	33.7

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire