

RAINIER W

MOUNTAIN SPORT

Giant's top-of-the-line recreational hardtail designed for women, the Rainier W is the perfect bike to explore your local trails.



SPECIFICATIONS

| FRAME | SIZES | 12.5(2XS), 14(XS), 16(S), 18(M) |
|------------|------------------|-----------------------------------|
| | COLORS | Olive/Brushed |
| | FRAME | ALUXX SL Aluminum |
| | FORK | RockShox Dart 3, 100mm w/ Lockout |
| | SHOCK | N/A |
| COMPONENTS | | |
| | HANDLEBAR | Alloy, 31.8mm high rise |
| | STEM | Alloy, 10 Degree Rise |
| | SEATPOST | Alloy, 350x30.9mm |
| | SADDLE | WTB Speed She Comp |
| | PEDALS | Alloy Platform |
| DRIVETRAIN | | |
| | SHIFTERS | SRAM X5 |
| | FRONT DERAILLEUR | Shimano Deore |
| | REAR DERAILLEUR | SRAM X5 |
| | BRAKES | Hayes MX-4 Disc |
| | BRAKE LEVERS | Tektro Alloy |
| | CASSETTE | Shimano HG-50 11/34T, 9-speed |
| | CHAIN | Shimano HG-73 |
| | CRANKSET | TruVativ ISO Flow 3.0, 22/32/42 |
| | BOTTOM BRACKET | TruVativ Power Spline |
| WHEELS | | |
| | RIMS | WTB Dual Duty XC, Double Wall |
| | HUBS | Formula 32H Disc |
| | SPOKES | Stainless Steel |
| | TIRES | Kenda Blue Groove/Nevegal 26x2.1 |
| | EXTRAS | |

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Giant's ALUXX SL aluminum-framed Rainier W features disc-brake capability and geometry optimized for 100mm of front-end suspension travel.

FEATURES

- RockShox Dart 3, 100mm suspension fork
- SRAM X.5 trigger shifting, Shimano X.5 rear derailleur
- Hayes MX-4 mechanical disc brakes, WTB Speed She Comp women's saddle
- WTB Dual Duty XC rim/Formula disc hub wheelset

FRAME GEOMETRY

| Actual Frame Size | Head Angle | Seat Angle* | Toptube** | Headtube | Chainstay | Wheelbase | Standover Height*** |
|-------------------|------------|-------------|-----------|----------|-----------|-----------|---------------------|
| inches | degrees | degrees | inches | inches | inches | inches | inches |
| 2XS/12.5 | 70.5 | 74.0 | 20.3 | 3.9 | 16.7 | 39.9 | 30.0 |
| XS/14 | 70.5 | 74.0 | 21.1 | 4.6 | 16.7 | 39.3 | 30.4 |
| S/16 | 70.5 | 73.5 | 21.6 | 4.6 | 16.7 | 40.9 | 29.5 |
| M/18 | 70.5 | 73.5 | 22.4 | 4.6 | 16.7 | 40.9 | 29.5 |

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire