

TCR W

ROAD COMPETITION

The same superb TCR racing geometry on an ALUXX SL aluminum frame. We've made getting to the front of the pack more affordable by offering a high level of performance at a great price.



SPECIFICATIONS

| FRAME | SIZES | 2XS, XS, S, M |
|------------|------------------|---|
| | COLORS | White/Red |
| | FRAME | ALUXX SL, Compact Road Design |
| | FORK | formulaOne Composite w / alloy steerer tube |
| | SHOCK | N/A |
| COMPONENTS | HANDLEBAR | Women's anatomic bend and drop, 31.8 |
| | STEM | 3D Forged Aluminum, 31.8 |
| | SEATPOST | formulaOne Composite |
| | SADDLE | WTB Deva women's saddle |
| | PEDALS | Crank Brothers, Candy C |
| DRIVETRAIN | SHIFTERS | Shimano Tiagra w / reach adjust |
| | FRONT DERAILLEUR | Shimano Tiagra |
| | REAR DERAILLEUR | Shimano Tiagra |
| | BRAKES | TK423AG, dual pivot |
| | BRAKE LEVERS | Shimano Tiagra |
| | CASSETTE | SRAM PG 950 11/26, 9-speed |
| | CHAIN | Shimano HG-53 |
| | CRANKSET | Shimano R4550-S, 34/50 |
| | BOTTOM BRACKET | Shimano, external |
| WHEELS | RIMS | Xero XSR - 3 |
| | HUBS | Xero XSR - 3 |
| | SPOKES | Xero XSR - 3 |
| | TIRES | Michelin Lithion, 700x23 |
| | EXTRAS | |

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Featuring a butted ALUXX SL aluminum frame and formulaOne Composite fork, the TCR W continues Giant's legendary Compact Road Design.



FEATURES

- Reliable 9-speed Shimano Tiagra shifting
- WTB Deva women's saddle with composite seatpost
- Crank Brothers Candy C pedals
- Women's-specific, narrow, shallow drop handlebar

FRAME GEOMETRY

| Actual Frame Size | Head Angle | Seat Angle* | Toptube** | Headtube | Chainstay | Wheelbase | Standover Height*** |
|-------------------|------------|-------------|-------------|-------------|-------------|-------------|---------------------|
| centimeters | degrees | degrees | centimeters | centimeters | centimeters | centimeters | inches |
| 2XS/41.0 | 71.5 | 74.5 | 51.0 | 13.0 | 40.5 | 96.5 | 27.1 |
| XS/43.0 | 71.0 | 74.0 | 51.5 | 12.5 | 40.5 | 96.7 | 28.5 |
| S/46.5 | 71.0 | 73.5 | 52.5 | 14.0 | 40.5 | 97.3 | 29.3 |
| M/50.0 | 73.0 | 73.5 | 54.0 | 15.5 | 40.5 | 97.0 | 30.2 |

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire