

XTC ALLIANCE

MOUNTAIN PERFORMANCE HARDTAIL

All-new for 2008, the Xtc Alliance features a perfect blend of composite and aluminum to create the ultimate hardtail experience. Lightweight. Stiff. Superior ride compliance.



SPECIFICATIONS

| FRAME | SIZES | XS, S, M, L, XL |
|------------|------------------|---|
| | COLORS | Brushed/White |
| | FRAME | Alliance |
| | FORK | Marzocchi MX Pro LO, 100mm w/ lockout |
| | SHOCK | N/A |
| COMPONENTS | | |
| | HANDLEBAR | Race Face Ride XC low rise, 31.8mm |
| | STEM | Race Face Ride XC, 6 degree rise |
| | SEATPOST | Race Face Ride XC, 350x30.9mm |
| | SADDLE | WTB Silverado Race |
| | PEDALS | Shimano PD-M520 |
| DRIVETRAIN | | |
| | SHIFTERS | SRAM X7, trigger |
| | FRONT DERAILLEUR | Shimano Deore |
| | REAR DERAILLEUR | SRAM X7 |
| | BRAKES | Hayes Stroker Ryde, 160F/160R |
| | BRAKE LEVERS | Hayes |
| | CASSETTE | SRAM PG 970, 11/34 9-speed |
| | CHAIN | Shimano HG-73 |
| | CRANKSET | Race Face Ride XC, 22/32/44 |
| | BOTTOM BRACKET | Race Face X-Type, external |
| WHEELS | | |
| | RIMS | WTB Dual Duty XC, Double Wall |
| | HUBS | Formula 32H Disc |
| | SPOKES | Stainless Steel |
| | TIRES | Kenda Small Block Eight 26x2.1/1.95 folding |
| | EXTRAS | |

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Giant's proprietary Alliance frame technology takes advantage of the performance benefits of both aluminum and composite. Through careful, seamless integration of these two materials, off-road riders of all levels can reap the benefits of increased comfort and performance from this unique blend.



FEATURES

- Marzocchi MX Pro, 100mm suspension fork
- SRAM X.7 trigger shifting, X.7 rear derailleur
- Hayes Stroker Ryde disc brakes
- WTB LaserDisc XC rim/Formula disc hub wheelset

FRAME GEOMETRY

| Actual Frame Size | Head Angle | Seat Angle* | Toptube** | Headtube | Chainstay | Wheelbase | Standover Height*** |
|-------------------|------------|-------------|-----------|----------|-----------|-----------|---------------------|
| inches | degrees | degrees | inches | inches | inches | inches | inches |
| XS/14.5 | 70.5 | 74.0 | 21.7 | 4.6 | 16.7 | 41.2 | 30.3 |
| S/16.0 | 70.5 | 73.5 | 22.6 | 4.6 | 16.7 | 41.8 | 30.6 |
| M/18.0 | 70.5 | 73.0 | 23.4 | 5.1 | 16.7 | 42.4 | 31.4 |
| L/20.0 | 70.5 | 73.0 | 24.2 | 5.7 | 16.7 | 43.2 | 32.4 |

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire