

CYPHER 1

Cypher gets you way out there—and brings you home. Whether it's a mountaintop summit or rugged singletrack, Maestro Suspension will help you float over the roughest trails and conquer the steepest climbs. It's the ultimate women's trail bike.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L	
	COLORS	Silver Anodized	
	FRAME	ALUXX SL-Grade Aluminum, 5.0" Maestro Suspension	
	FORK	Fox 32 F120RL, 120mm travel w/ 15QR Thru Axle	
COMPONENTS	SHOCK	Fox Float RP2	
	HANDLEBAR	Race Face Evolve XC Low Rise, 31.8	
	STEM	Race Face Evolve XC	
	SEATPOST	Race Face Evolve XC, 350x30.9mm	
	SADDLE	WTB Deva Comp	
	PEDALS	Crank Brothers Smarty, Custom for Giant	
	DRIVETRAIN	SHIFTERS	Shimano XT Rapidfire
		FRONT DERAILLEUR	Shimano SLX
		REAR DERAILLEUR	Shimano XT Shadow, top normal
BRAKES		Shimano XT, 180F/160R	
BRAKE LEVERS		Shimano XT	
WHEELS	CASSETTE	SRAM PG 980 11/34, 9-speed	
	CHAIN	Shimano HG-73	
	CRANKSET	Shimano XT, 22/32/44	
	BOTTOM BRACKET	Shimano XT, External	
	RIMS	WTB Laser Disc Trail	
	HUBS	[F] Giant Sealed/CNC Disc for 15MM Axle, [R] Formula Alloy Sealed Disc	
	SPOKES	DT Competition, 14/15g	
	TIRES	Kenda Nevegal, 26x2.1 Folding	
	EXTRAS		

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Keep your momentum on climbs, and feel that rear tire engage through the lightweight ALUXX SL frame and 5 inches of Maestro suspension luxuriousness. Thrill to faster descents, helped by the plush suspension fork and light-action disc brakes. With Cypher, you're absolutely covered, uphill or down.



KEY UPGRADES (OVER CYPHER 2)

- Fox 32 F120RL 120mm suspension fork w/ 15QR thru-axle, Fox Float RP2 rear shock
- Shimano Deore XT drivetrain and hydraulic disc brakes
- Race Face Evolve XC handlebar, stem and seatpost
- WTB LaserDisc Trail rim/Giant Tracker hub/WTB hub/DT Competition spokes, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
XS/14.5	349442	69.5	74.0	21.1	4.9	17.1	41.8	30.9
S/16	349443	69.5	73.5	21.7	5.3	17.1	42.2	31.1
M/18	349444	69.5	73.5	22.2	5.9	17.1	42.8	31.8
L/20	349445	69.5	73.5	23.0	6.7	17.1	43.7	32.0

*Seat angle is effective

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire