

# ROAD PERFORMANCE

## DEFY 2

It's a new year, and an all-new Defy. Race-inspired engineering with an all-new tubeset from the world leader in aluminum technology. Defy is lighter to help with the climbs, stiffer to maximize power transfer and just plain faster than its closest competitor.



### SPECIFICATIONS

FRAME	SIZES	XS,S,M,M/L,L,XL
	COLORS	Red/Silver/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Advanced-Grade Composite, Alloy OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Giant Alloy Anatomic Bend, 31.8
	STEM	Giant Alloy 4-bolt
	SEATPOST	Giant Composite, 30.9
	SADDLE	Giant Performance Road, Men's
	PEDALS	Caged w/ Clips
DRIVETRAIN	SHIFTERS	Shimano Sora
	FRONT DERAILLEUR	Shimano Sora
	REAR DERAILLEUR	Shimano Tiagra
	BRAKES	Tektro R350 Dual Pivot
	BRAKE LEVERS	Shimano Sora
	CASSETTE	Shimano HG50, 12/25, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	FSA Omega, 30/39/50
	BOTTOM BRACKET	FSA Mega Exo, External
WHEELS	RIMS	Mavic CXP22
	HUBS	Formula sealed Cartridge Bearing 24/28h
	SPOKES	SAPIM Race, 14/15g
	TIRES	Kenda Kriterium, 700x25
EXTRAS		

Specifications and availability subject to change without notice.

### FRAME TECHNOLOGY

Ride like a pro on the most advanced ALUXX SL aluminum frame yet. Giant flexes some engineering muscle to produce a lighter, stiffer tubeset than before, with better ride tuning, so you get the best of everything.



### KEY UPGRADES (OVER DEFY 3)

- 9-speed Shimano Sora shifting
- Composite seatpost
- Lighter Mavic CXP22 rims, Formula sealed hubs/SAPIM race spokes, wheelset

### FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	383052	71.0	74.0	51.5	12.5	42.0	98.3	29.0
S/46.5 cm	383053	72.0	74.0	53.0	14.5	42.0	99.0	29.7
M/50.0 cm	383054	72.5	73.0	54.5	16.5	42.0	99.0	30.6
M/L/53.5 cm	383055	72.5	73.0	56.0	18.5	42.0	100.5	31.1
L/55.5 cm	383056	72.5	72.0	57.5	20.5	42.0	100.8	32.0
XL/58.5 cm	383057	72.5	72.0	59.5	22.5	42.0	102.8	32.8

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire