

## FCR 3

Ditch the treadmill, take it outside and go beyond the gym with FCR. Upright, flat-bar positioning makes this a road racer that's been tamed just enough to make it comfortable in the city.



### SPECIFICATIONS

FRAME	SIZES	XS,S,M,L,XL
	COLORS	Black
	FRAME	ALUXX-Grade Aluminum
	FORK	CroMo
COMPONENTS	SHOCK	N / A
	HANDLEBAR	Alloy lowrise
	STEM	Alloy adjustable height, 25.4
	SEATPOST	Giant Alloy, 27.2
DRIVETRAIN	SADDLE	Giant Unity SuperSoft Venture, Men
	PEDALS	Caged w/ Clips
	SHIFTERS	Shimano R221 EZ Fire
	FRONT DERAILLEUR	Shimano R443
WHEELS	REAR DERAILLEUR	Shimano Altus
	BRAKES	Alloy Direct Pull Cantilever
	BRAKE LEVERS	Shimano Alloy
	CASSETTE	SRAM PG 830 11/28, 8-speed
EXTRAS	CHAIN	KMC Z72
	CRANKSET	FSA Vero, 30/42/52
	BOTTOM BRACKET	Cartridge
	RIMS	Alloy 32H, Double Wall
	HUBS	Alloy 32H
	SPOKES	Stainless Steel
	TIRES	Kenda Kwest, 700x28
	EXTRAS	

Specifications and availability subject to change without notice.

### FRAME TECHNOLOGY

The lightweight ALUXX frameset and wide-range gearing tame steep city inclines, while the quick handling reflexes and flat bar let you sling corners with precision. Tuned ride comfort meets road racer efficiency.



### FEATURES

- Wide-range 8-speed Shimano shifting with FSA Vero triple crankset
- Giant Unity SuperSoft Venture saddle
- Confident-handling Kenda Kwest 700x28c tires

### FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	380052	71.0	75.0	52.5	12.5	42.5	100.9	29.5
S/46.5 cm	380053	72.0	74.0	54.5	14.5	42.5	101.0	30.3
M/50.0 cm	380054	72.5	73.0	56.5	17.0	42.5	102.5	31.3
L/55.5 cm	380055	72.5	73.0	58.5	20.0	42.5	103.5	32.8
XL/58.5 cm	380056	72.5	72.5	60.5	22.5	42.5	104.9	33.7

\*Seat angle is actual

\*\*Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

\*\*\*Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire