

REIGN XO

Big rocks, sick drops, log crossings—Reign X rules it all with true full-suspension confidence. If you thrive on that jagged line between all-mountain and pure downhill, this is your machine. Ride *anywhere* there's a possible line.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L
	COLORS	Champaign Anodized
	FRAME	ALUXX SL-Grade Aluminum, 6.7" Maestro Suspension
	FORK	Fox 36 Float RC2, 160mm travel w/ 20mm Thru Axle
COMPONENTS	SHOCK	Fox DHX 4.0, air
	HANDLEBAR	Race Face Atlas low rise, 31.8
	STEM	Race Face Atlas AM
	SEATPOST	Crank Brothers Joplin Adjustable, 382x30.9mm
	SADDLE	WTB Pure V Race
DRIVETRAIN	PEDALS	Crank Brothers Acid 1.0
	SHIFTERS	SRAM X9 trigger w/ Matchmaker Clamp
	FRONT DERAILLEUR	Shimano SLX w/ Race Face Atlas Shiftguide
	REAR DERAILLEUR	SRAM X0
	BRAKES	Avid Elixir CR 180F/160R
	BRAKE LEVERS	Avid Elixir CR
	CASSETTE	SRAM PG 980 11/34, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Race Face Atlas, 24/36/RG
	BOTTOM BRACKET	Race Face X Type, External
WHEELS	RIMS	WTB LaserDisc Trail
	HUBS	WTB LaserDisc Lite w/ 20mm Super duty front
	SPOKES	DT Competition, 14/15g
	TIRES	WTB Prowler MX/XT, 26x2.3
	EXTRAS	Large has 180R rotor

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Reign X's 6.7 inches of always-active Maestro Suspension let you pound pedals uphill and blitz down. Buttressed, hydro-formed, perfectly welded ALUXX SL aluminum and the best suspension on the trail make this the ultimate all-mountain machine.



KEY UPGRADES (OVER REIGN X1)

- Fox 36 Float RC2 160mm suspension fork, Fox DHX 4.0 air rear shock
- SRAM X.9 shifters/X.0 rear derailleur with Avid Elixir CR disc brakes
- Crank Brothers Joplin adjustable seatpost
- WTB LaserDisc Trail rim/WTB LaserDisc Lite 20mm hub wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
XS/15	346842	67.0	72.5	22.0	4.6	17.3	43.7	31.7
S/16	346843	67.0	72.5	22.4	4.6	17.3	44.1	31.5
M/18	346844	67.0	72.5	23.2	5.0	17.3	44.9	30.7
L/20	346845	67.0	72.0	24.1	5.9	17.3	45.7	31.0

*Seat angle is effective

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire