

TCR ADVANCED SL 0

All new. All race. All conquering. That's the TCR Advanced SL. Developed for the pro ranks, tested in the world's toughest races from the Spring Classics to the Tour de France and the choice of High Road's Team Columbia. Ready to ride. Ready to rip. Ready to win.



SPECIFICATIONS

FRAME	SIZES	XS,S,M/L,L,XL
	COLORS	Composite/Red
	FRAME	Advanced SL-Grade Composite, Integrated Seatpost
	FORK	Advanced SL-Grade Composite, Full Composite OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	FSA K-Force Carbon, 31.8
	STEM	FSA K-Force OS-99
	SEATPOST	Advanced SL-Grade Composite, Integrated Design
	SADDLE	Fizik Arione CX w/ Braded Composite rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	SRAM Red
	FRONT DERAILLEUR	SRAM Red
	REAR DERAILLEUR	SRAM Red
	BRAKES	SRAM Red
	BRAKE LEVERS	SRAM Red
	CASSETTE	SRAM Red 11-25, 10-speed
	CHAIN	SRAM PC-1090
	CRANKSET	SRAM Red Carbon, 39/53
WHEELS	BOTTOM BRACKET	SRAM GXP, Internal Press Fit
	RIMS	MAVIC Cosmic Carbone SLR
	HUBS	MAVIC Cosmic Carbone SLR
	SPOKES	MAVIC Cosmic Carbone SLR
	TIRES	Michelin Pro Race3, 700x23
	EXTRAS	2 ISP clamps provided : Regular 20mm & XL 40mm

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Giant's lightest, stiffest, fastest road racer ever. Handcrafted, engineered precision creates the new benchmark for pedaling stiffness and efficiency. From its sleek integrated seatpost to the massive MegaDrive rectangular downtube and oversized toptube, this is pure Advanced SL-grade composite performance. Without compromise.



KEY UPGRADES (FROM TCR ADVANCED SL 1)

- SRAM Red component group
- FSA K-Force handlebar and stem
- Lighter Mavic Cosmic Carbone SLR wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	387342	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S/46.5 cm	387343	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	387344	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	387345	73.0	72.0	57.0	17.0	40.5	98.6	31.0
L/55.5 cm	387346	73.0	72.0	58.5	18.5	40.5	100.1	31.7
XL/58.5 cm	387347	73.0	72.0	60.5	20.0	40.5	102.1	32.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire