

TCR ADVANCED SL TEAM

All new. All race. All conquering. That's the TCR Advanced SL. Developed for the pro ranks, tested in the world's toughest races from the Spring Classics to the Tour de France and the choice of High Road's Team Columbia. Ready to ride. Ready to rip. Ready to win.



SPECIFICATIONS

FRAME	SIZES	XS,S,M/M/L,L,XL
	COLORS	Composite/Silver
	FRAME	Advanced SL-Grade Composite, Integrated Seatpost
	FORK	Advanced SL-Grade Composite, Full Composite OverDrive Steerer
	SHOCK	N / A
COMPONENTS	HANDLEBAR	Shimano PRO VIBE OS Composite, 31.8
	STEM	Shimano PRO PLT Composite
	SEATPOST	Advanced SL-Grade Composite, Integrated Design
	SADDLE	Selle Italia SLR-XP w/ Vanox rails
	PEDALS	Not Included
DRIVETRAIN	SHIFTERS	Shimano Dura-Ace 7900
	FRONT DERAILLEUR	Shimano Dura-Ace 7900
	REAR DERAILLEUR	Shimano Dura-Ace 7900
	BRAKES	Shimano Dura-Ace 7900
	BRAKE LEVERS	Shimano Dura-Ace 7900
	CASSETTE	Shimano Dura-Ace 7900 12/25, 10-speed
	CHAIN	Shimano Dura-Ace 7900
	CRANKSET	Shimano Dura-Ace 7900, 39/53
	BOTTOM BRACKET	Shimano Dura-Ace, Internal Press Fit
	WHEELS	RIMS
HUBS		Shimano Dura-Ace carbon WH-7850-C24-CL
SPOKES		Shimano Dura-Ace carbon WH-7850-C24-CL
TIRES		Schwalbe Ultrero, 700X23
EXTRAS		2 ISP clamps provided : Regular 20mm & XL 40mm

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Giant's lightest, stiffest, fastest road racer ever. Handcrafted, engineered precision creates the new benchmark for pedaling stiffness and efficiency. From its sleek integrated seatpost to the massive MegaDrive rectangular downtube and oversized toptube, this is pure Advanced SL-grade composite performance. Without compromise.



KEY UPGRADES (FROM TCR ADVANCED SL O)

- Full Shimano Dura-Ace 7900 component group
- Shimano PRO handlebar and stem
- Featherweight Shimano Carbon Dura-Ace wheels

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
centimeters		degrees	degrees	centimeters	centimeters	centimeters	centimeters	inches
XS/43.0 cm	387252	71.0	74.5	52.0	12.0	40.5	97.7	28.5
S/46.5 cm	387253	72.0	73.5	53.5	13.5	40.5	97.4	29.2
M/50.0 cm	387254	73.0	73.0	55.5	15.0	40.5	98.0	30.1
M/L/53.5 cm	387255	73.0	72.0	57.0	17.0	40.5	98.6	31.0
L/55.5 cm	387256	73.0	72.0	58.5	18.5	40.5	100.1	31.7
XL/58.5 cm	387257	73.0	72.0	60.5	20.0	40.5	102.1	32.4

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire