

TCX 0

Get down and dirty on a TCX. Whether it's hopping curbs or hopping barriers, the all-new TCX won't let you down. It's the ultimate cyclocrosser or urban speedster, ready for mud, barriers, storm drain grates and obstacles, on the racecourse or anywhere.



SPECIFICATIONS

| | | |
|------------|------------------|---|
| FRAME | SIZES | S,M,L,XL |
| | COLORS | White/Team Blue/Black |
| | FRAME | ALUXX SL-Grade Aluminum |
| | FORK | Advanced-Grade Composite, Alloy OverDrive Steerer |
| | SHOCK | N / A |
| COMPONENTS | HANDLEBAR | Race Face Cadence, 31.8 |
| | STEM | Race Face Cadence |
| | SEATPOST | Giant Composite, 30.9 |
| | SADDLE | Fi'zi:k Aliante Delta |
| | PEDALS | Crank Brothers Egg Beater SL |
| DRIVETRAIN | SHIFTERS | Shimano Ultegra |
| | FRONT DERAILLEUR | Shimano Ultegra |
| | REAR DERAILLEUR | Shimano Ultegra |
| | BRAKES | Tektro CR-720 specific cyclocross |
| | BRAKE LEVERS | Shimano Ultegra |
| | CASSETTE | Shimano 105 12/25, 10-speed |
| | CHAIN | Shimano 105 |
| | CRANKSET | FSA Energy MegaExo Compact, 36/46 |
| | BOTTOM BRACKET | FSA Mega Exo, External |
| WHEELS | RIMS | Mavic Aksium |
| | HUBS | Mavic Aksium |
| | SPOKES | Mavic Aksium |
| | TIRES | Michelin Cross Mud2 TS, 700X30 Folding |
| | EXTRAS | Top Bar Tektro RL721 specific cyclocross brake |

FRAME TECHNOLOGY

Pure speed, for all conditions. Stable geometry and gobs of mud clearance let you go where road bikes can't. The all-new superlight ALUXX SL aluminum frame with top-routed cables makes it easy to tackle all obstacles, no matter the conditions.



KEY UPGRADES (FROM TCX 1)

- Shimano Ultegra 10-Speed shifting
- Race Face Cadence handlebar/stem and Fi'zi:k Aliante Delta saddle
- Lighter Mavic Aksium wheelsset with Michelin Cross Mud tires

FRAME GEOMETRY

| Actual Frame Size | Part Number | Head Angle | Seat Angle* | Toptube** | Headtube | Chainstay | Wheelbase | Standover Height*** |
|-------------------|-------------|------------|-------------|-------------|-------------|-------------|-------------|---------------------|
| centimeters | | degrees | degrees | centimeters | centimeters | centimeters | centimeters | inches |
| S/49 cm | 385163 | 71.0 | 73.5 | 53.5 | 13.5 | 43.0 | 101.9 | 30.5 |
| M/51.5 cm | 385164 | 72.0 | 73.0 | 55.5 | 15.0 | 43.0 | 102.5 | 31.5 |
| L/55.5 cm | 385165 | 72.0 | 72.0 | 58.5 | 18.5 | 43.0 | 104.6 | 32.5 |
| XL/58.5 cm | 385166 | 72.0 | 72.0 | 60.5 | 20.0 | 43.0 | 106.6 | 34.0 |

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire