

TCX 1

Get down and dirty on a TCX. Whether it's hopping curbs or hopping barriers, the all-new TCX won't let you down. It's the ultimate cyclocrosser or urban speedster, ready for mud, barriers, storm drain grates and obstacles, on the racecourse or anywhere.



SPECIFICATIONS

| | | |
|------------|------------------|---|
| FRAME | SIZES | S,M,L,XL |
| | COLORS | White/Red/Black |
| | FRAME | ALUXX SL-Grade Aluminum |
| | FORK | Advanced-Grade Composite, Alloy OverDrive Steerer |
| | SHOCK | N / A |
| COMPONENTS | HANDLEBAR | AL Anatomic Bend, 31.8 |
| | STEM | Giant Alloy |
| | SEATPOST | Giant Composite, 30.9 |
| | SADDLE | Giant Performance Road, Men's |
| | PEDALS | Crank Brothers Egg Beater MXR |
| DRIVETRAIN | SHIFTERS | Shimano 105 |
| | FRONT DERAILLEUR | Shimano 105 |
| | REAR DERAILLEUR | Shimano 105 |
| | BRAKES | Tektro CR-720 specific cyclocross |
| | BRAKE LEVERS | Shimano 105 |
| | CASSETTE | Shimano 105 12/25, 10-speed |
| | CHAIN | Shimano 105 |
| | CRANKSET | FSA Gossamer MegaExo Compact, 36/46 |
| | BOTTOM BRACKET | FSA Mega Exo, External |
| WHEELS | RIMS | Mavic CXP 22N black |
| | HUBS | Formula sealed Cartridge Bearing 24/28h |
| | SPOKES | SAPIM Race, 14/15g |
| | TIRES | Kenda Small Block Eight, 700x35 Folding |
| | EXTRAS | Top Bar Tektro RL721 specific cyclocross brake |

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Pure speed, for all conditions. Stable geometry and gobs of mud clearance let you go where road bikes can't. The all-new superlight ALUXX SL aluminum frame with top-routed cables makes it easy to tackle all obstacles, no matter the conditions.



KEY UPGRADES (FROM TCX 2)

- Shimano 105 10-speed shifting with FSA Gossamer Mega Exo 46/35 crankset
- Composite seatpost and OverDrive, light weight composite fork
- Mavic CXP22 rims, Formula sealed hubs/SAPIM race spokes, wheelset

FRAME GEOMETRY

| Actual Frame Size | Part Number | Head Angle | Seat Angle* | Toptube** | Headtube | Chainstay | Wheelbase | Standover Height*** |
|-------------------|-------------|------------|-------------|-------------|-------------|-------------|-------------|---------------------|
| centimeters | | degrees | degrees | centimeters | centimeters | centimeters | centimeters | inches |
| S/49 cm | 385063 | 71.0 | 73.5 | 53.5 | 13.5 | 43.0 | 101.9 | 30.5 |
| M/51.5 cm | 385064 | 72.0 | 73.0 | 55.5 | 15.0 | 43.0 | 102.5 | 31.5 |
| L/55.5 cm | 385065 | 72.0 | 72.0 | 58.5 | 18.5 | 43.0 | 104.6 | 32.5 |
| XL/58.5 cm | 385066 | 72.0 | 72.0 | 60.5 | 20.0 | 43.0 | 106.6 | 34.0 |

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire