

TRANCE XO

Farther, faster, longer—if that's your goal when you hit the trail, Trance X will get you there. With an ALUXX SL alloy frame and Maestro's fully-active rear suspension you'll go the distance, quickly, with energy to spare for the ride home.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L,XL
	COLORS	Gray Anodized
	FRAME	ALUXX SL-Grade Aluminum, 5.0" Maestro Suspension
	FORK	Fox 32 Talas RLC, 100 -140 mm travel w/ 15QR Thru Axle
COMPONENTS	SHOCK	Fox Float RP23
	HANDLEBAR	Race Face Next SL 3/4" low rise, 31.8
	STEM	Race Face Deus SL
	SEATPOST	Race Face Next SL 350x30.9mm
	SADDLE	Fi'zi:k Gobi XM w/ Nicro Rails
DRIVETRAIN	PEDALS	Crank Brothers Candy 2Ti
	SHIFTERS	Shimano XTR Rapidfire
	FRONT DERAILLEUR	Shimano XTR
	REAR DERAILLEUR	Shimano XTR, top normal
	BRAKES	Avid Elixir CR Carbon, 180F/160R
	BRAKE LEVERS	Avid Carbon
	CASSETTE	Shimano XTR 11/34, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano XTR, 22/32/44
	BOTTOM BRACKET	Shimano XTR, External
WHEELS	RIMS	Mavic CrossMax ST Disc
	HUBS	Mavic CrossMax ST w/ 15mm Front Axle
	SPOKES	Mavic CrossMax ST
	TIRES	Kenda Nevegal, 26x2.1 Folding
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Trance X is cutting-edge superiority with features like a hyper-engineered main triangle, absolutely dialed geometry and 5 inches of Maestro Suspension that's active under pedaling and braking alike. But all you need to know is this: Trail riding just got that much better.



KEY UPGRADES (OVER TRANCE X1)

- Full-featured Fox 32 Talas RLC 100-140mm suspension fork with 15QR thru axle, Fox Float RP23 rear shock
- Shimano XTR drivetrain/shifting with Avid Elixir CR Carbon disc brakes
- Race Face Next SL handlebar and seatpost
- Fi'zi:k Gobi XM saddle and Crank Brothers Candy 2Ti pedals

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
XS/14.5	347042	69.5	73.5	21.5	4.7	17.1	41.9	30.5
S/16	347043	69.5	73.5	22.0	5.1	17.1	42.6	30.9
M/18	347044	69.5	73.5	23.0	5.7	17.1	43.6	31.4
L/20	347045	69.5	73.5	24.0	6.5	17.1	44.6	32.0
XL/22	347046	69.5	73.5	25.0	7.5	17.1	45.7	32.4

*Seat angle is effective

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire