

TRANCE X3

Farther, faster, longer—if that's your goal when you hit the trail, Trance X will get you there. With an ALUXX SL alloy frame and Maestro's fully-active rear suspension you'll go the distance, quickly, with energy to spare for the ride home.



SPECIFICATIONS

FRAME	SIZES	XS,S,M,L,XL
	COLORS	Blue/Silver
	FRAME	ALUXX SL-Grade Aluminum, 5.0" Maestro Suspension
	FORK	Fox 32 F120R, 120mm travel w/ 15QR Thru Axle
COMPONENTS	SHOCK	Fox Float R
	HANDLEBAR	Race Face Ride XC low rise, 31.8
	STEM	Race Face Ride XC
	SEATPOST	Race Face Ride XC 350x30.9mm
	SADDLE	WTB Devo Team
	PEDALS	Crank Brothers Smarty, Custom for Giant
	DRIVETRAIN	SHIFTERS
FRONT DERAILLEUR		Shimano Deore
REAR DERAILLEUR		Shimano SLX, top normal
BRAKES		Hayes Stroker Ryde Custom for Giant 180F/160R
BRAKE LEVERS		Hayes
WHEELS	CASSETTE	Shimano HG50 11/34, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Race Face Ride XC, 22/32/44
	BOTTOM BRACKET	Race Face X Type, External
	RIMS	WTB LaserDisc Trail
	HUBS	[F] Giant Tracker Sealed/CNC Disc w/ 15mm Axle, 32H [R] Formula Alloy Sealed Disc, 32H
	SPOKES	[F]15G [R]14g Stainless
	TIRES	Kenda Nevegal, 26x2.1 Folding
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Trance X is cutting-edge superiority with features like a hyper-engineered main triangle, absolutely dialed geometry and 5 inches of Maestro Suspension that's active under pedaling and braking alike. But all you need to know is this: Trail riding just got that much better.



KEY UPGRADES (OVER TRANCE X4)

- Fox 32 F120R 120mm suspension fork w/ 15QR thru-axle, Fox Float R rear shock
- Hayes Stroker Ryde custom hydraulic disc brakes
- Race Face Ride XC handlebar, stem and seatpost
- WTB LaserDisc Trail rim/Giant Tracker hub/Formula hub, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches		degrees	degrees	inches	inches	inches	inches	inches
XS/14.5	344542	69.5	73.5	21.5	4.7	17.1	41.9	30.5
S/16	344543	69.5	73.5	22.0	5.1	17.1	42.6	30.9
M/18	344544	69.5	73.5	23.0	5.7	17.1	43.6	31.4
L/20	344545	69.5	73.5	24.0	6.5	17.1	44.6	32.0
XL/22	344546	69.5	73.5	25.0	7.5	17.1	45.7	32.4

*Seat angle is effective

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire