

XTC 29ER 2

ROLL THROUGH THE STICKEST TRAIL SITUATIONS WITH CONFIDENCE AND CONTROL. THE BENEFITS OF LARGER WHEELS WITHOUT COMPROMISE.



SPECIFICATIONS

FRAME	SIZES	S,M,L,XL
	COLORS	Brushed Smoke/Black
	FRAME	ALUXX SL-Grade Aluminum
	FORK	Marzocchi Forty-Niner TST2 w/15QR Thru Axle and tapered steerer, 100mm travel
SHOCK		N / A
COMPONENTS	HANDLEBAR	Giant Connect, riser 31.8
	STEM	Giant Connect
	SEATPOST	Giant Connect, 375x30.9
	SADDLE	Fi'zi:k Tundra w/ Manganese rails
	PEDALS	Giant Alloy Platform
DRIVETRAIN	SHIFTERS	Shimano Deore
	FRONT DERAILLEUR	Shimano Deore
	REAR DERAILLEUR	Shimano Deore Shadow, top normal
	BRAKES	Shimano Alivio 160mm
	BRAKE LEVERS	Shimano Alivio
	CASSETTE	Shimano HG61 12x36, 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	Shimano Alivio, 22/32/44
BOTTOM BRACKET		Shimano BB-ES25, Sealed Cartridge
WHEELS	RIMS	Giant P29, AluXX Double wall alloy*
	HUBS	[F] Giant Tracker Sealed w/ 15mm Axle, [R] Formula, 32h
	SPOKES	Stainless Steel, 14g
	TIRES	Kenda Karma, 29x2.0 Folding
	EXTRAS	*Rims design is compatible with aftermarket tubeless conversion systems

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

The all-new Xtc 29er brings precise trail-handling and agility to the world of 29-inch wheels. With highly engineered ALUXX SL aluminum tubing and performance XC geometry, it has both predictable stability and surprising snappiness. Add in Giant's all-new, ultra-stiff P29 rim and 29er-specific flat handlebar, and it's the ideal way to tackle any XC racecourse or weekend epic.



FEATURES

- Marzocchi Forty-Niner TST2, 15mm through axle, tapered-steerer fork
- Shimano Deore shifting
- Shimano Alivio disc brakes
- Giant Tracker 15mm through-axle hub/ Stainless spokes/ Giant P29 rim, wheelset

FRAME GEOMETRY

Actual Frame Size	Part Number	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
<i>inches</i>		<i>degrees</i>	<i>degrees</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>	<i>inches</i>
S/16	333473	71.0	73.0	22.4	3.5	17.3	41.8	28.5
M/18	333474	71.5	72.5	23.4	3.9	17.3	42.4	29.6
L/20	333475	71.5	72.5	24.2	3.9	17.3	43.2	30.5
XL/22	333476	71.5	72.5	25.0	4.7	17.3	44.0	31.6

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire